

# Coil Nailer



## PT-CN55

### Applications

Crating & Box Assembly, Decking, Pallet Manufacturing, Pallet Repair, Sheathing, Subflooring

### Specifications

Diameter	.083" - .092"
Nail Range	1" to 2-1/4"
Head Diameter	.215" - .224"
Capacity	300 Nails
Firing Mode	Bump
Dimensions	12" x 5" x 12"
Weight	5 lbs 15 oz
Air Pressure	70-100 p.s.i.

### Features

360° Exhaust Direction, Body Protector, Comfort Grip, 'Contact Mode' Safety System, Metal Nail Tray, Narrow Nose for Accurate Nail Placement, Protective Dust Cover, Tough Nylon Magazine, Well Balanced

### Includes

Safety Glasses, Tool Oil, Manual, Parts Diagram



For Best Results Use Spotnails® Collated Fasteners

Stock Number	Size	Description	M/ Bx	Bx/ Cs	M/ Cs
<b>.083 Flat Coil</b>					
CW3D083R	1-1/4 X .083	Ring, Bright, Flat	14.0	30.8	48
CW3D083RG	1-1/4 X .083	Ring, Galv, Flat	14.0	31.0	48
CW4D083R	1-1/2 X .083	Ring, Bright, Flat	14.0	35.6	48
CW4D083RG	1-1/2 X .083	Ring, Galv, Flat	14.0	33.3	48
CW5D083R	1-3/4 X .083	Ring, Bright, Flat	11.2	32.3	48
CW5D083RG	1-3/4 X .083	Ring, Galv, Flat	11.2	31.1	48
CW5D083S	1-3/4 X .083	Screw, Flat	11.2	32.4	48
CW6D083R	2 X .083	Ring, Bright, Flat	11.2	37.1	48
CW6D083RG	2 X .083	Ring, Galv, Flat	11.2	37.9	48
CW7D090RG-4.2M	2-1/4 X .090	Ring, Galv, Flat	4.2	18.9	84
<b>Wire Weld Fencing/Siding Nails - 304 SS</b>					
CW4D090SSR-3.6M	1-1/2" X .090	304 SS, Ring	3.6	11.7	144
CW5D090SSR-3.6M	1-3/4" X .090	304 SS, Ring	3.6	12.8	128
CW5.5D090SSR-3.6M	1-7/8" X .090	304 SS, Ring	3.6	13.6	112
CW6D090SSR-3.6M	2" x .090	304 SS, Ring	3.6	14.8	112
CW7D090SSR-3.6M	2-1/4" x .090	304 SS, Ring	3.6	16.7	112
<b>.092 Flat - Hot Dipped Galvanized</b>					
CW3D092RHDG	1-1/4" X .092	Ring, HDG	3.6	10.0	132
CW4D092RHDG	1-1/2" X .092	Ring, HDG	3.6	12.0	120
CW5D092RHDG	1-3/4" X .092	Ring, HDG	3.6	14.4	108
CW6D092RHDG	2" X .092	Ring, HDG	3.6	16.7	96
CW7D092RHDG	2-1/4" X .092	Ring, HDG	3.6	19.9	96



Division of Peace Industries, LTD.  
 Phone: 800-873-2239 \* Fax: 888-369-2588  
 nailerparts.com \* partskrafters.com  
 spotnails.com \* redhawkfasteners.com

